two Müller Martini trimming units with three knife trimmer for sizes A5 and A4 of

set of conveyor belts and delivery: straightening equipment type 0365.04124



Curriculum Vitae of the machine Reference number: X 11623







ALBERT FRANKENTAL

Gravure / Rotogravure Printing Machine

SPECIAL OFFER

1980 Production Year: More Details: rotogravure machine including pre-press line with accessories and spare parts, Number of Colours: machine is suitable for print of glazed or satin paper of weight 45-90 gr/m2. Web-width: 1920 mm min./max. width paper roll 1420-1920 mm, circumference of the form cylinder Cylinders Circumference: 1420 mm from 860 to 1420 mm, 710 mm Cut-off: maximum mechanical speed 30000 revolutions of form cylinder per hour, Number of Reels: maximum paper speed 12,2 m/sec., maximum production speed 30 000 at 4U a 20 000 at 6U revolution/hour. Max. Speed: 30000 imp./hour number of pages 6U 72,60, 56,48,40,32,28,24, number of pages 4U 48,24,32,16 pages, immediately Availability: basic part of machine: 1 pc of roll winder, 9 pcs of printing aggregates, Work Experiences: commercial magazine 1 pc of folding unit including additional folding and sewing equipment, printing Roll winder with automatic change (blocking of roll bushes integrated to winder Sale Reason: purchase of a new holders of paper roll, machine pneumatic control, electric control. functional, complete Condition of the Machine: electronic axial shifting of central axis of winder rolls, can be seen running control group for paper tension, electro-motorise rotation of rolls carrier with two speeds, well-maintained Refurbishments: printing aggregates (reverse) with chamber doctor blade 10-40 mm, side register speed 0.33 mm. good opprtunity Machinery Europe's Opinion: longitudinal register 1 mm/sec., to purchase complete ink tank for each printing aggregate, electrostatic print support Eltex, line from pre-press each aggregate equipped with cooling equipment, folding unit (system 5/4) consists of retract roller, to press rotogravure machine set of retract rollers, owner needs to move conveyor for sheet transportation, the machine asap security equipment, electric tachometer, additional folding unit consists of main registers rollers, Disclaimer: The Condition of the towing kits, Machine assessment presented in this CV was longitudinal cutting with dust exhausting, sewing equipment model CC with two sewing heads, wire thickness 0,6 mm. either obtained from the Accessories: last machine operator or

finished product,

is based on an

possible.

inspection performed by

our employee, just to provide you with as much information as

For more certainty we

recommend your own check or an assessment of an independent mechanic. We cannot provide you with any machine guarantee.