

Curriculum Vitae of the machine Reference number: X 11623



ALBERT FRANKENTAL Gravure / Rotogravure Printing Machine

SPECIAL OFFER

Production Year:	1980
Number of Colours:	5
Web-width:	1920 mm
Cylinders Circumference:	1420 mm
Cut-off:	710 mm
Number of Reels:	1
Max. Speed:	30000 imp./hour

Availability: immediately

Work Experiences: commercial magazine printing

Sale Reason: purchase of a new machine



Condition of the Machine: functional, complete can be seen running

Refurbishments: well-maintained

Machinery Europe's Opinion: good opportunity to purchase complete line from pre-press to press rotogravure machine owner needs to move the machine asap

Disclaimer: The Condition of the Machine assessment presented in this CV was either obtained from the last machine operator or is based on an inspection performed by our employee, just to provide you with as much information as possible. For more certainty we

More Details:

rotogravure machine including pre-press line with accessories and spare parts, machine is suitable for print of glazed or satin paper of weight 45-90 gr/m2. min./max. width paper roll 1420-1920 mm, circumference of the form cylinder from 860 to 1420 mm, maximum mechanical speed 30000 revolutions of form cylinder per hour, maximum paper speed 12,2 m/sec., maximum production speed 30 000 at 4U a 20 000 at 6U revolution/hour, number of pages 6U 72,60, 56,48,40,32,28,24, number of pages 4U 48,24,32,16 pages, basic part of machine: 1 pc of roll winder, 9 pcs of printing aggregates, 1 pc of folding unit including additional folding and sewing equipment, specification: Roll winder with automatic change (blocking of roll bushes integrated to winder holders of paper roll, pneumatic control, electric control, electronic axial shifting of central axis of winder rolls, control group for paper tension, electro-motorise rotation of rolls carrier with two speeds, printing aggregates (reverse) with chamber doctor blade 10-40 mm, side register speed 0,33 mm, longitudinal register 1 mm/sec., ink tank for each printing aggregate, electrostatic print support Eltex, each aggregate equipped with cooling equipment, folding unit (system 5/4) consists of retract roller, set of retract rollers, conveyor for sheet transportation, security equipment, electric tachometer, additional folding unit consists of main registers rollers, towing kits, longitudinal cutting with dust exhausting, sewing equipment model CC with two sewing heads, wire thickness 0,6 mm. Accessories: two Müller Martini trimming units with three knife trimmer for sizes A5 and A4 of finished product, set of conveyor belts and delivery: straightening equipment type 0365.04124

recommend your own
check or an assessment
of an independent
mechanic. We cannot
provide you with any
machine guarantee.
