

Curriculum Vitae of the machine Reference number: 26012



GALLUS R 250 F Flexographic Printing Machine

SPECIAL OFFER

Production Year: 1989
Number of Colours: 4

Availability: immediately

Work Experiences: self-adhesive materials,
paper, cardboard

Sale Reason: production reduction



Condition of the Machine: functional, condition and wear and tear according to its age, well maintained not in daily production but can be seen running at your request

Disclaimer: The Condition of the Machine assessment presented in this CV was either obtained from the last machine operator or is based on an inspection performed by our employee, just to provide you with as much information as possible. For more certainty we recommend your own check or an assessment of an independent mechanic. We cannot provide you with any machine guarantee.

More Details:

belt speed:
speed during setting: 5 m/min
maximum speed belt: 150 m/min
reduction of the maximum speed belt when integrating the following units:
rotary letterpress unit: max. 100 m/min
flat die-cutting unit:
at die-cutting length 315 mm: 104 m/min
at die-cutting length 157 mm: 52 m/min
rotary dry printing unit: 45 m/min
rotary screen printing unit: 35 m/min
material thickness: 0.05 – 0.33 mm
flat weight: 80 – 300 g/m²
unwinding:
belt width: max. 280 mm / min. 130 mm
roll diameter: max. 1000 mm
winding:
roll diameter
winding unit max. 700 mm
automatic winding 3 spindles max. 380 mm
grid exhaust unit max. 800 mm
stacking:
belt width max. 280 mm
format length
stacking unit max. 460 mm
Schuppen - delivery max. 305 mm
printing:
printing width max. 260 mm
printing length max. 609.6 mm / min. 304.8 mm
setting step 3.175 mm
flat die-cutting:
die-cutting width max. 270 mm
die-cutting length max. 314.325 mm / min. 157.163 mm
setting step 1.59 mm
rotary cutting:
cutting width max. 270 mm
cutting length max. 609.6 mm / min. 304.8 mm
setting step 3.175 mm
rotary punching:
cutting width max. 260 mm
cutting length max. 609.6 mm / min. 508 mm
setting step 3.175 mm

